

Label printers XC4/XC6



■ Standard □ Option ○ Possible

For two-color printing

Two in-line arranged thermal transfer print units are printing one label simultaneously with two colors. Due to the ribbon saver at one print unit the ribbon consumption of the additional colored ribbon is reduced. The XC series meets the conditions for the Classification and Labeling Inventory according to GHS. Large label rolls up to a diameter of 300 mm can be converted. The two print units with ribbon holder, operation panel and electronics are adopted from the proven A+ series.

Label printer		XC4	XC6
Print head	Printing method	Thermal transfer	
	Print resolution dpi	300	
	Print speed up to mm/s	125	
	Print width up to mm	105,6	162,6
Material	External diameter up to mm	300	
	Label width mm	20 – 116	46 – 176
	Label height mm	20 – 2000	20 – 1500
Ribbon	Ink	outside or inside	
	Length up to m	360	
	Ribbon saver printhead 2	■	
Dimensions	Height x Depth x Width mm	395 x 554 x 248	395 x 554 x 358
Electronics	Processor speed MHz	266	
	(RAM) MB	64	
	Memory IFFS MB Flash	8	
	Slot for CF card type I	■	
	Slot for wireless LAN card	■	
Interfaces	USB 2.0 High Speed device for PC	■	
	Ethernet 10/100 Base T	■	
	Peripheral connection	■	
	WLAN card 802.11 b/g	□	
	2x USB Host for external operation panel, keyboard, scanner, USB stick, service key		
Accessories	Cutter	□	□
	Perforation cutter	○	–
	Stacker with cutter	□	–
	External rewinder	□	□
	External unwinder	□	□