

DJ45



Straight forward design of message and print control by a touch interface
One controller supports two 12.7 mm heads

Salient Features

- One controller supports two hp TIJ2.5 print heads, the Anti-shock mechanism protects print head on production line.
- External photocell instead of built-in sensor with flexibility to print in diverse applications. (Encoder is optional)
- A diverse range of inks available for coding onto various substrates even non-porous
- Cartridge hot-swap quick changeover.
- Capability of connecting external data via RS232 to print.

Electrical Requirements	: AC 100V ~ 240V, 50/60Hz
Operating Temperature	: 5° C - 45° C (41° F -112° F)
Weight	: 1645g (excluding cartridge)
Dimensions	: Controller (L/W/H) 205 x 140 x 68 (mm) Print Head (L/W/H) 130 X 115 X 94 (mm)
Mounting Orientation	: Horizontal or downside
Message Storage	: Capacity to store up to 999 messages
Data Interface	: RS232 & USB port
Ink Throw Distance	: 6mm - 9mm, depends on the ink type
Print Resolution & Print Speed	: DJ45A - 30m/min at 300 dpi (Max. print head cable 2 meters) DJ45B - 60m/min at 300dpi (Max. print head cable 1 meter)
Max. print length	: 1 meter

Marketed in India by



sales@jayinst.com
www.jayinst.com

JAY INSTRUMENTS AND SYSTEMS PRIVATE LIMITED

Head Office :

E-16, Everest, Tardeo Road,
Mumbai - 400 034.
Tel. : +91-22-2352 6207 / 8,
Fax. : +91-22-2352 6210

Navi Mumbai Office :

C-64, TTC - Industrial Area, Turbhe,
Navi Mumbai - 400 703.
Tel. : +91-22-2767 2955 / 0092,
Fax. : +91-22-2767 0161

Branches : Ahmedabad, Bengaluru, Chennai, Delhi, Hubballi, Hyderabad, Tirupur.